Stickers International

www.stickersinternational.com

Technical Datasheet - Window Stickers

Vinyl - Gloss Clear Static Cling

Thickness: 175 micron (0.17mm)
Thickness Film: 75 micron
Thickness Glue/Coating: 25 micron
Weight: 225 g/m²

Adhesive type: Static cling

Excellent transparency properties
Adheres to flat glossy surfaces without adhesive
Easy to remove, without residue, and re-use
Suitable for indoor use for up to 3 years, not recommended for outdoor usage
The surface needs to be cleaned properly before applying - do not use cleaning liquids containing alcohol
To avoid fingerprints, usage of cotton gloves is recommended

Minimum application temperature +10˚C

Shelf life: 1 year

Vinyl - Gloss Clear Self-Adhesive

Face film: Calendered Vinyl
Thickness: 70 micron (0.07mm)
Tensile strength: 50N/25mm MD / 48N/25mm TD
Elongation at break: 180% MD
Adhesive type: Permanent clear solvent-based acrylic
Adhesive weight: 18gsm
Adhesion to glass 20 mins: 10N/25mm
Adhesion to glass 24 hours: 20N/25mm
Perceived tack: Medium
Application temperature: +10°C to +60°C
Service temperature: -30°C to +110°C
Backing paper weight: 140gsm
Shelf life: 1 year
Fire rating: Class B. BS EN 13501-1:2007
External weathering: 5 years

Disclaimer: Product performance should always be tested in the actual application conditions. We cannot assume any liability for damage caused through the use of our products as they are used in conditions beyond our control.